





EVIS ZEIT / ZUTRITTSLESER

EVIS AG
Elektronische Systeme
Hölzliwisenstrasse 5
CH- 8604 Volketswil
Tel: +41 (0)44 908 11 11
Fax: +41 (0)44 908 11 12
www.evis.ch
info@evis.ch
Verkauf Deutschland
info-de@evis.ch



		EVIS EDI 4200	EVIS IBIS	EVIS EDI 4200 PIN	EVIS EDI 4200 TOUCH	EVIS IBIS PIN	LIFTLERANTENNE	EVIS ZARGENLESER
Varianten UP	RS485	263012	263050	263016	263020	263051	209117	COMING SOON
	RS232	263013	-	263017	263021	-	-	-
	RJ45 / Ethernet / LAN	263014	-	263018	263022	-	-	-
	Relais / stand alone	263015	-	263019	263023	-	-	-
EVIS Firmware	Im Partnerbereich downloadbar	2005XXXX	2005XXXX	2005XXXX	2005XXXX	2005XXXX	2005XXXX mit Troll	2005XXXX
Zubehör	AP-Rahmen	890266	890266	890266	890266	890266	Standartmässig wird die Liftleserantenne mit einer Troll Einbauplatine eingesetzt. Troll RS485, 261203	-
	AP-Rahmen / RJ45	890267	890267	890267	890267	890267		-
	NUP / IP 55 / Feller	890280 + 611253	890280 + 611254	890280 + 611259	890280 + 611258	890280 + 611249		-
	NAP / IP55 / Feller	890281 + 611253	890281 + 611254	890281 + 611259	890281 + 611258	890281 + 611249		-
	EVIS BE0	280460	280460	280460	280460	280460		280460
Eigenschaften	LED-Multicolor	-	x	-	-	x	-	x
	LED-Ampelsteuerung	x	-	x	x	-	-	-
	Summer	x	x	x	x	x	x	x
	PIN-Code-Tastatur	-	-	x	berührungsempfindlich	x	-	x
RFID	LEGIC ® prime	x	x	x	x	x	x	x
	LEGIC ® advant	x	x	x	x	x	x	x
	MIFARE ® Classic	x	x	x	x	x	x	x
	MIFARE ® DESFire®	x	x	x	x	x	x	x
Protokolle	EVIS 3rd Party	RS485, RS232, LAN	x	RS485, RS232, LAN	RS485, RS232, LAN	x	x	x
	EVIS Frame	RS485, RS232, LAN	x	RS485, RS232, LAN	RS485, RS232, LAN	x	x	x
	BPA9	RS485, LAN	x	RS485, LAN	RS485, LAN	x	x	x
	OSDP	RS485, LAN	x	RS485, LAN	RS485, LAN	x	x	x
	Wiegand	RS232	-	RS232	RS232	-	-	-
	Seriell Simplex (Omron)	RS485, RS232, LAN	-	RS485, RS232, LAN	RS485, RS232, LAN	-	x	-
	Kundenspezifisch	x	x	x	x	x	x	x
Stromversorgung	8 - 17 VAC	x	-	x	-	-	-	-
	8 - 24 VDC	x	-	x	x	-	-	-
	8 - 30 VDC	-	-	-	x	-	-	-
	10 - 40 VDC	-	x	-	-	x	-	x
	200mA	x	-	x	x	-	-	-
	Abgesetzte Antenne	-	-	-	-	-	x	-
Besondere Merkmale	Kundenspez. Frontfolie	x	x	x	x	x	-	x
	Sabotagekontakt	x	x	x	x	x	x	x
	Schraubklemmen fest	x	-	x	x	-	-	-
	Schraubklemmen steckbar	-	x	-	x	-	-	x
	UID, ISO 14443, ISO 15693 Transponder auslesen	x	x	x	x	x	x	x
Auslesbar	via NFC, HCE, Servicetool	x	x	x	x	x	x	x
Konfigurierbar	via NFC, HCE, Servicetool, Parameterkarte	x	x	x	x	x	x	x
Datenträger	Rondo, Metallica, Karten	x	x	x	x	x	x	x